

DC POWER SUPPLIES

SINGLE VARIABLE OUTPUT



0 to 5 volts, 0 to 5 amps
0 to 5 volts, 0 to 10 amps

TESTRONIX 30C
TESTRONIX 30D

0 to 16 volts, 0 to 2 amps
0 to 16 volts, 0 to 5 amps
0 to 16 volts, 0 to 10 amps

TESTRONIX 34B
TESTRONIX 34C
TESTRONIX 34D

0 to 32 volts, 0 to 1 amp
0 to 32 volts, 0 to 2 amps
0 to 32 volts, 0 to 5 amps
0 to 32 volts, 0 to 10 amps

TESTRONIX 92A
TESTRONIX 92B
TESTRONIX 92C -
TESTRONIX 92D

0 to 65 volts, 0 to 1 amp
0 to 65 volts, 0 to 2 amps
0 to 65 volts, 0 to 5 amps

TESTRONIX 36A
TESTRONIX 36B
TESTRONIX 36C

OUTPUT VOLTAGES : The output voltage is continuously adjustable by coarse and fine controls and is displayed on 3 ½ digit, LED display of 12.5 mm height with accuracy of $\pm 0.5\% \pm 2$ least counts. (Voltmeters in models 30C/ 30D/ 92A/ 92B/ 92C/ 92D/ 36A/ 36B/ 36C have 3 digit displays.) Output voltage can be floated on any live voltage or any of the two voltage terminals can be grounded to get positive or negative voltage.

LOAD CURRENT : Load current is displayed on 3½ digit, LED display of 12.5mm height, with accuracy of $\pm 0.5\% \pm$ least counts. (Current meters in models 30C/ 34C/ 36C have 3 digit displays.) Maximum value of output current can be limited from less than 10% to 100% of the capacity by continuously adjustable coarse and the controls.

PROTECTION : Short circuit and overload protected. Constant voltage constant current type of regulation provides constant voltage if load current is less than current limit setting. If load tries to draw more current than the value of current limit setting, current becomes constant at the limit setting and output voltage comes down to limit the current at the limit setting value.

REGULATION : $\pm 0.05\%$ from no load to full load and for $\pm 10\%$ variations in input mains voltage.

RIPPLES : Less than 3 milli volts rms.

POWER REQUIREMENTS : $230 \pm 10\%$ VAC, 50/60 hertz. Power consumption is 1.5 times multiple of maximum voltage rating and load current drawn.

SIZE AND WEIGHT :

125mm (H) x 125mm(W) x 270mm(D), 3.5kgs for 30C/34B/92A.
135mm (H) x 195mm(W) x 270mm(D), 5kgs for 30D/34C/92B/36A/36B.
135mm (H) x 360mm(W) x 270mm(D), 9.5kgs for 34D/92C
225mm (H) x 255mm(W) x 300mm(D), 14kgs for 92D/36C

STANDARD ACCESSORIES : Test leads and instruction manual.

DUAL VARIABLE OUTPUT (INDEPENDENT AND TRACKING)



0 to ± 16 volts dual, 0 to 2 amps
0 to ± 32 volts dual, 0 to 5 amps

TESTRONIX 35B
TESTRONIX 93C

OUT PUT VOLTAGES : Two independent (both positive or both negative or, one positive and one negative) output voltages of different values or of same values are available in independent mode of operation. Two tracking output voltages of equal value and opposite polarities are available in dual tracking mode of operation. Independent or dual tracking mode is selected by front panel control. The output voltages are continuously adjustable by coarse and fine front panel controls. Two output voltages are continuously displayed on 2 separate 3 ½ digit meters with accuracy of $\pm 0.5 \pm 2$ least counts. (Meters have 3 digit in model 930). Meters have LED displays of 12.5 mm height. Output voltages can be floated on any live voltage or any of the terminals of the output voltage can be grounded to get positive or negative voltages.

LOAD CURRENT : Load currents of both the outputs are displayed on two separate 3 ½ digit meters with accuracy of $\pm 0.5\% \pm 2$ least counts. (Meters have 3 digits in model 93C). Meters have LED type of displays of 12.5mm height. Maximum values of output currents can be limited from less than 10% to 100% of the full capacity by continuously adjustable coarse and fine controls.

PROTECTION : Short circuit and overload protected. Constant voltage, constant current type of regulation provides constant voltage if load current is less than the current limit setting. If load tries to draw more current than the value of current limit setting, current becomes constant at the limit setting and output voltage comes down to limit the current at the current limit setting value.

REGULATION : $\pm 0.05\%$ from no load to full load and for $\pm 10\%$ variations in input mains voltage.

RIPPLES : Less than 3 mill volts r.m.s.

POWER REQUIREMENT : $230 \pm 10\%$ volts AC, 50/60 Hertz. Power consumption is 1.5 times the multiple of maximum voltage rating with the sum of the load currents drawn.

SIZE & WEIGHT : 175 mm (H) x 245mm (W) x 270mm (D), 5kgs for 35B. 255mm (H) x 255mm (W) x 300mm (D), 13.5kgs for 93C.

STANDARD ACCESSORIES : 2 pairs of test leads and instruction manual.

T extra at 12.5% Freight at actuals extra.