

# CM-2070C & CM-2070FT

## Digital Clamp Meter

**HTC**<sup>TM</sup>  
**INSTRUMENTS**

### Features:

- 3 1/2 Auto range Clamp Meter.
- Full Function Protection, Strong anti-interferential Performance.
- CLAMP OPEN: 52mm.
- Clamp Light and backlight display.
- Temperature & NCV.
- Frequency Test (For CM-2070FT)



| Function                  | Range                                     | Accuracy  |
|---------------------------|---|-----------|
| DC VOLTAGE (DCV)          | 200 mV ~ 1000 V                           | ±(0.5%+5) |
| AC VOLTAGE (ACV)          | 200 mV ~ 750 V                            | ±(1.0%+5) |
| AC Current (ACA)          | 200A                                      | ±(2.0%+5) |
|                           | 1000A                                     |           |
| Resistance (Ω)            | 200Ω / 2KΩ / 20KΩ /<br>200KΩ / 2MΩ / 20MΩ | ±(0.8%+3) |
| Temperature               | (-40 ~ 1000) °C                           | ±(1.0%+5) |
|                           | (0 ~ 1832) °F                             | ±(1.0%+5) |
| Frequency (For CM-2070FT) | 100 Hz ~ 10 MHz                           | ±(0.5%+5) |

- **Standard Accessories** : Test leads, Battery, Manual, TP01 Temperature probe
- **Dimension** : 123(H) x270(W) x 35(D)mm

