



27-AUTO



27T-AUTO



2502T-AUTO

<b>400A AC</b>	
Auto Ranging, 3½ Digit 2000 Counts, Data Hold, Max, NCV, APO	
<b>Ranges</b>	
<b>AC Current</b>	2A, 20A, 200A, 400A (Auto Ranging)
Accuracy	±(3%rdg+5dgt) on 2A ±(2%rdg+3dgt) on 20A ±(2%rdg+5dgt) on 200A & 400A
Overload	400A AC max. for 1 min.
<b>AC Voltage</b>	2V, 20V, 200V, 600V (Auto Ranging)
Accuracy	±(1.2%rdg+3dgt)
<b>DC Voltage</b>	200mV, 2V, 20V, 200V, 600V (Auto Ranging)
Accuracy	±(0.8%rdg+3dgt)
<b>Resistance</b>	200Ω, 2kΩ, 20KΩ, 200kΩ, 2MΩ, 20MΩ (Auto Ranging)
Accuracy	±(1.2%rdg+3dgt)
<b>Audible Continuity</b>	40Ω Approx
<b>Diode Test Function</b>	1.0 ±0.6mA Approx
<b>Power</b>	Two 1.5'AAA' Size Batteries
<b>Battery Life</b>	200 Hours Typical
<b>Low Battery</b>	"" is indicated
<b>Dimension</b>	185 x 65 x 28 mm
<b>Weight</b>	170gms Including Battery (approx.)
<b>Accessories</b>	One pair of Test Leads, Instruction Manual, Carrying Case, Battery (installed)
<b>Jaw Opening</b>	Cable Dia. 25mm (max.)
<b>Safety Standard</b>	CAT II 600V

<b>400A AC</b>	
Auto Ranging, 3½ Digit 2000 Counts, Temperature, Data Hold, Max, NCV, APO	
<b>Ranges</b>	
<b>AC Current</b>	2A, 20A, 200A, 400A (Auto Ranging)
Accuracy	±(3%rdg+5dgt) on 2A ±(2%rdg+3dgt) on 20A ±(2%rdg+5dgt) on 200A & 400A
Overload	400A AC max. for 1 min.
<b>AC Voltage</b>	2V, 20V, 200V, 600V (Auto Ranging)
Accuracy	±(1.2%rdg+3dgt)
<b>DC Voltage</b>	200mV, 2V, 20V, 200V, 600V (Auto Ranging)
Accuracy	±(0.8%rdg+3dgt)
<b>Temperature</b>	-20°C to 750°C
Accuracy	±(3%rdg+5dgt)
<b>Resistance</b>	200Ω, 2kΩ, 20KΩ, 200kΩ, 2MΩ, 20MΩ (Auto Ranging)
Accuracy	±(1.2%rdg+3dgt)
<b>Audible Continuity</b>	40Ω Approx
<b>Diode Test Function</b>	1.0 ±0.6mA Approx
<b>Power</b>	Two 1.5'AAA' Size Batteries
<b>Battery Life</b>	200 Hours Typical
<b>Low Battery</b>	"" is indicated
<b>Dimension</b>	185 x 65 x 28 mm
<b>Weight</b>	170gms Including Battery (approx.)
<b>Accessories</b>	One pair of Test Leads, Instruction Manual, Carrying Case, Battery (installed) K Type Thermocouple (upto 260°C)
<b>Jaw Opening</b>	Cable Dia .25mm (max.)
<b>Safety Standard</b>	CAT II 600V

<b>1000A AC</b>	
Auto / Manual, 3½ Digit 2000 Counts, Temperature, Data Hold, Max, NCV, APO	
<b>Ranges</b>	
<b>AC Current</b>	2A, 20A, 200A, 1000A
Accuracy	±(3%rdg+5dgt) on 2A & 20A ±(2%rdg+5dgt) on 200A & 1000A
Overload	1000A AC max. for 1 min.
<b>AC Voltage</b>	2V, 20V, 200V, 750V
Accuracy	±(1.2%rdg+3dgt)
<b>DC Voltage</b>	200mV, 2V, 20V, 200V, 1000V
Accuracy	±(0.8%rdg+3dgt)
<b>Temperature</b>	-20°C to 750°C
Accuracy	±(3%rdg+5dgt)
<b>Resistance</b>	200Ω, 2kΩ, 20KΩ, 200kΩ, 2MΩ, 20MΩ
Accuracy	±(1.2%rdg+3dgt)
<b>Audible Continuity</b>	30Ω Approx
<b>Diode Test Function</b>	1.0 ±0.6mA Approx
<b>Power</b>	Two 1.5V 'AA' Size Batteries
<b>Battery Life</b>	200 Hours Typical
<b>Low Battery</b>	"" is indicated
<b>Dimension</b>	245 x 95 x 35 mm (approx.)
<b>Weight</b>	309gms Including Battery (approx.)
<b>Accessories</b>	One pair of Test Leads, Instruction Manual, Carrying Case, Battery (installed) K Type Thermocouple (upto 260°C)
<b>Jaw Opening</b>	Cable Dia .52mm (max.)
<b>Safety Standard</b>	CAT III 600V

